

PACIFIC FRIEND



BUILDERS/ YEAR: Honda Heavy Industries 2007

FLAG/ CALL SIGN/ IMO/ MMSI: Hong Kong/VRCW6 / 9392626/ 477829500

HOME PORT: Hong Kong

CLASS/ NOTATION: Class NK/ HK-1915

MANAGERS:

COMMERCIAL: Thorco Shipping A/S

TECHNICAL: P&F Marine – Korea

P&I: GARD



TONNAGE:

- DWT Incl. TWD 12121 ton
- GT/NT 9684 / 3810
- Suez 8862,23 NT

TYPE:

- Multipurpose general cargo vessel, Flush tween deck, removable, semi box hold

DIMENSION:

- Length 120,0 MT
- LPP 106,5 MT
- Beam 21,20 MT
- Draft 8,51 MT
- Air draft 30,59 MT

TANK CAPACITY:

- HFO 817,9 M3
- MGO 168,35 M3
- Ballast 2365,42 M3
- FW 513,07 M3

CARGO HOLD # 1 CAPACITY:

- **Floor space**
 - Tank top 646,16 m2
 - Tween deck 788,50 m2
 - Hatch cover 450 m2
- **Volume hold 1**
 - Grain 10359,83 m3
 - Bale 10068,27 m3
- **Permissible Loads**
 - Tank top 12 MT uniform
 - Tank top 15 MT local
 - Tween deck 3,7 MT
 - Hatch cover 1,5 MT

HOLD EQUIPMENT:

- Electrical ventilation
- Air hoist for shifting tween deck cover
- Dehumidifier fitted in hold
- CO2 fitted.
- Grain fitted
- Fitted for carrying dangerous goods

CARGO HOLD # 2 CAPACITY:

- **Floor space**
 - Tank top 642,6 m2
 - Tween deck 775,20 m2
 - Hatch 450,0 m2
- **Volume hold 2**
 - Grain 10216,72 m3
 - Bale 9820,34 m3
- **Permissible Loads**
 - Tank top 12 MT uniform
 - Tank top 15 MT local
 - Tween deck 3,77 MT
 - Hatch cover 2,49 MT

HOLD EQUIPMENT:

- Electrical ventilation
- Air hoist for shifting tween deck covers.
- Dehumidifier fitted in the hold
- CO 2 fitted
- Grain fitted.
- Fitted for carrying dangerous goods

CARGO GEAR:

- 2 x Electro-hydraulic cranes
- Positioned mid ships
- 2 x Derricks in forepart & aft part of the cargo holds.
- **Lifting capacity**
 - Crane 1 & 2
 - SWL 30,7 ton á 31 MT
 - Twin opr SWL 60 ton á 31 MT
 - Derricks SWL 25 to á 22 MT, maximum outreach from ships side is 4,5 MT

ENGINES:

- Two Stroke engine 3900 kW at 210 rpm burning IFO 380cst.
- Axillary engines
- 2 x 355 KW á 1200 rpm

CONTAINERS:

- **Hatch 1 & 2**
 - 24 TEU
 - Total 48 TEU

Pacific Friend

